



DECIACAMP- C

DESCRIPTION

DECIACAMP-C allows you to draw white lines on turf without causing irritation as it is free of Calcium Hydroxide. Can be used with all the spray marking machines on the market.

DECIACAMP C is a READY TO USE product designed to have characteristics of excellent stability when stored, adherence to the turf, high visibility, excellent whiteness and excellent coverage.

DECIACAMP-C is also available in the colors Red, Blue, Green, Yellow and dark green.

PHYSICAL CHEMICAL CHARACTERISTICS

COLOUR	white,red,blue,green,yellow and dark green
ASPECT	opaque
COMPOSITION	natural charges
SPECIFIC WEIGHT	1,20 ± 0,05 g/cm ³ at 20 °C
VISCOSITY	10000 ± 2000 cps R5 rpm 12
DRY EXTRACT	39 ± 2%

Note: These properties are typical and should not be considered specific. Marginal deviations in values affect neither the efficiency nor the properties of the product.

APPLICATION METHOD

APPLICATION TEMPER.	+5 / +35 Celsius
DRYING TIME	15/20 min. (at 20°C and 65 U.R.)
DILUTION	ready to use
APPAREIL	airless
PERFORMANCE:	5 lt of product for a regular soccer field (variable value depending on the nozzles used in the painting phase and application speed)

Note: These properties are typical and should not be considered specific. Marginal deviations in values affect neither the efficiency nor the properties of the product.

APPLICATION TOOLS

mix the paint before use, adjust the equipment according to the requirements of the application or the condition of the grass.

SUPPORT	turf
----------------	------

PACKAGE

plastic bucket It 10

GENERAL NOTE

The product is sensitive to frost. It is advisable to keep it at a temperature between + 5 ° and + 25 ° C. Stored in the original packaging, sealed and undiluted with water, it has a long storage period.

All of the above technical information contained in this sheet is the result of accurate laboratory tests and practical experience. They do not represent a legal warranty, express or implied, regarding the use of our product, which is used outside our control. Each user must check the effectiveness and behavior of our product vis-à-vis its specific applications