



DECIACAMP ROLL

DESCRIPTION

DECIACAMP-ROLL allows you to draw white lines on turf without causing irritation as it is free of calcium hydroxide. Can be used with all roller tracking machines on the market. Product designed to have characteristics of adhesion to the turf, high visibility, excellent whiteness and coverage.

DECIACAMP ROLL is also available in the colors Red, Blue, Green, Yellow.

PHYSICAL CHEMICAL CHARACTERISTICS

COLOUR	white
ASPECT	opaque
COMPOSITION	natural charges
SPECIFIC WEIGHT	$1,47 \pm 0,05 \text{ g/cm}^3$ a 20 °C
VISCOSITY	$680 \pm 200 \text{ cps R5 rpm 200}$
DRY EXTRACT	$45 \pm 2\%$

Note: These properties are typical and should not be considered specific. Marginal deviations in values affect neither the efficiency nor the properties of the product.

APPLICATION METHOD

APPLICATION TEMPER.	+5 / +35 Celsius
DRYING TIME	$\pm 30 \text{ min. (at } 20^\circ\text{C and } 65 \text{ U.R.)}$
DILUTION	ready to use
ÉQUIPEMENT	roll paint tool for line marking
SUPPORT	natural turf , grass
PERFORMANCE:	10 liters of product for a regulation football field (variable value depending on the wear of the striper rollers)

Note: These properties are typical and should not be considered specific. Marginal deviations in values affect neither the efficiency nor the properties of the product.

APPLICATION TOOLS

Mix carefully the paint before use, adjust the equipment according to the requirements of the application or the condition of the grass.

SUPPORT	natural grass
PACKAGE	plastic bucket It 10

GENERAL NOTE

The product is sensitive to frost. It is advisable to keep it at a temperature between + 5 ° and + 25 ° C. Stored in the original packaging, sealed and undiluted with water, it has a long storage period.

All of the above technical information contained in this sheet is the result of accurate laboratory tests and practical experience. They do not represent a legal warranty, express or implied, regarding the use of our product, which is used outside our control. Each user must check the effectiveness and behavior of our product vis-à-vis its specific applications