

DECIA WOOD S

Versione 1.1.0 - 2023

DESCRIPTION

Colorless, pigmented single-component woodworm preservative impregnating agent designed for the protection of both interior and exterior wood. Its main distinguishing features are its high penetration, ease of application and pleasant matte finish. It does not flake and allows the wood to breathe. It is also the ideal base for painting with WAXED DECIA WOOD S.

CHEMICAL AND PHYSICAL CHARACTERISTICS

COLOR colorless, folder tints

FILM APPEARANCE Transparent, enhances wood grain

COMPOSITION Oil-alkali resin 850 g/l at 20 °C

VISCOSITY Ford cup 2 55" at 20°C

FLASH POINT 33° C **AUTOIGNITION** 427° C

Note: These properties are typical ones and are not to be considered specific. Marginal deviations of the values do not affect the efficacy or property of the product.

APPLICATION CHARACTERISTICS

TEMP. OF APPLICATION between + 5 and + 30 °C.

DRYING dry to the touch 1 hour. Complete 12/24 hours depending on the

wood and environmental conditions.

YIELD 8 - 15 sqm/l depending on the absorption of the substrate.

DILUTION ready to use. **APPLICATION EQUIPMENT** brush and spray

APPLICATION SYSTEM.

Ideal for treating fences, wooden cottages, garden furniture and wood in general Make sure the substrate is sound, dry and properly sanded.

Mix the product well before use.

Apply one or more coats of Decia Wood S respecting the drying time.

On old wood already treated with impregnating agent, clean the surface of dust and apply one or more coats of Decia Wood S.

Note: Successful application cycles are conditioned by proper preparation of the substrate. What is described in the sheet represents a minimum condition that should be supplemented to the professionalism and experience of the operator

SAFETY REGULATIONS.

Refer to the safety data sheet for information on storage, handling and proper disposal of the product

PACKAGING LT 10 - 2.5 - 750 ML

WARNINGS

Store the product in a cool, dry place. Shelf life minimum 12 months in tightly sealed original packaging. Shake the product thoroughly before use.

All of the above technical information contained within this sheet, is the result of careful laboratory tests and practical experience. They do not represent a legal warranty, expressed or implied, about the use of our product as used outside of our control. Each user should verify the effectiveness and behavior of our product with regard to its specific applications.