



# DECIA WOOD

Versione 1.1.0 - 2023

## DESCRIPTION

High-penetration water-based impregnating agent ideal for the protection of wooden artifacts both indoors and outdoors. The careful formulation makes parts treated with Decia wood excellently protected from weathering, mold and pests. Decia wood does not flake, but it does wear off, making maintenance easier, as all that is needed is to remove surface dirt and apply one or more coats of Decia wood. CARATTERISTICHE CHIMICHE FISICHE

<b>COLOR</b>	Colorless, folder tints
<b>FILM APPEARANCE</b>	Transparent, enhances wood grain
<b>COMPOSITION</b>	binder based on acrylic resin emulsion
<b>SPECIFIC WEIGHT</b>	1.02 ± 0.03 kg/l at 20 °C
<b>VISCOSITY</b>	19 ± 4 cup DIN 4 at 20°C

Note: These properties are typical ones and are not to be considered specific. Marginal deviations in the values do not affect the effectiveness or properties of the product.

## APPLICATION CHARACTERISTICS

<b>TEMP. OF APPLICATION</b>	between + 5 and + 30 °C
<b>DRYING</b>	dry to touch 1 hour, Complete 12/24 hours depending on the wood and environmental conditions.
<b>YIELD</b>	8 - 12 sqm/l depending on the absorption of the substrate.
<b>DILUTION</b>	ready to use
<b>APPLICATION EQUIPMENT</b>	brush

## APPLICATION SYSTEM

Ideal for treating fences, wooden cottages, garden furniture and wood in general

Make sure the substrate is sound, dry and properly sanded.

Mix the product well before use.

Apply one or more coats of Decia wood respecting the drying time.

On old wood already treated with impregnating agent, clean the surface of dust and apply one or more coats of Decia wood.

Note: Successful application cycles are conditioned by proper preparation of the substrate. What is described in the sheet represents a minimum condition that must be supplemented by the professionalism and experience of the operator.

## **SAFETY REGULATIONS**

Refer to the safety data sheet for information on storage, handling and proper disposal of the product

## **PACKAGING**

LT 10 - 2.5 - 750 ML

## **WARNINGS**

The product is sensitive to frost. Do not apply at temperatures below 5°C.  
Shake the product thoroughly before use

All of the above technical information contained within this sheet, is the result of careful laboratory tests and practical experience. They do not represent a legal warranty, expressed or implied, about the use of our product as used outside of our control. Each user should verify the effectiveness and behavior of our product with regard to its specific applications.