

DESCRIPTION

White pigmented fixative sealer. Its application evens out the absorption of substrates and facilitates subsequent coats of finish. Based on aqueous emulsions, it is suitable for old, new surfaces and plasterboard. DECIABLANK is characterized by high coverage, opacity and filler.

PHYSICAL CHEMICAL CHARACTERISTICS

COLOR	white
ASPECT	liquid
COMPOSITION	binder based on aqueous emulsions.
SPECIFIC WEIGHT	1.30 ± 0.05 g/cm ³ at 20 °C
VISCOSITY	3200 ± 1000 cps R6 rpm 60

Note: These properties are typical ones and are not to be considered specific. Marginal deviations in the values do not affect the effectiveness or properties of the product.

APPLICATION CHARACTERISTICS

TEMP. OF APPLICATION	between +5 and +25 degrees °C
DRYING	3-5 hours (referred to 20°C and 65% R.H.)
YIELD	9-12 m ² /l depending on substrate
DILUTION	30-40% with potable water depending on the substrate

APPLICATION EQUIPMENT brush - roller

APPLICATION SYSTEM

SUPPORTS: interior masonry work

SUBSTRATE PREPARATION: The substrate must be sound, dry, clean, free of salt efflorescence, and free of moisture stains and mold. Old chalking paints should be removed by pressure washing. Do not apply to fresh or particularly alkaline substrates; observe a minimum carbonation period of at least four weeks. Imperfections, cracks, will have to be restored using MURAPLASTER.

Note: Successful application cycles are conditioned by proper preparation of the substrate. What is described in the sheet represents a minimum condition that should be supplemented to the professionalism and experience of the operator.

APPLICATION CYCLE

NEW PLASTERS apply one coat of DECIABLANK suitably diluted with potable water, complete the cycle with the most suitable finish.

OLD PLASTERS see "PREPARATION OF THE SUBSTRATE." Proceed with the finishing as for "NEW PLASTERS."

NOTE mix well before use.

SPECIFICATION ITEM

GENERAL FEATURES pigmented fixative based on aqueous emulsions.
SPECIFIC WEIGHT 1.30 ± 0.05 g/cm³ at 20 °C.

PACKAGING

PACKAGING plastic buckets lt 14 - 5 - 2.5 - 0.75

GENERAL NOTES

The product is sensitive to frost. It is recommended, to store it at temperatures between +5° and +25°C. Stored in the original tightly closed packages, and undiluted with water, it has a medium storage period. Avoid application to fresh or particularly alkaline substrates, observing a minimum period of at least four weeks.

Use potable water for dilution and maintain the same proportions throughout application.

All of the above technical information contained within this sheet is the result of careful laboratory tests and practical experience. They do not represent a legal warranty, expressed or implied, about the use of our product as used outside of our control. Each user should verify the effectiveness and behavior of our product with regard to its specific applications.