

DESCRIPTION

Decordecia is the new line of decorative products from Colorificio Valdecia.

Product formulated totally water-based with careful selection of raw materials used is offered in four versions: gold, copper, silver, and neutral.

In the gold, copper and silver version, in addition to the metallic effect typical of the base itself with the addition of the appropriate colorants, infinite shades can be obtained.

In the neutral version with the addition of the appropriate dyes, the effects of classic glazing are obtained.

It is also possible to add in all bases the glitters of Colorificio Valdecia, which with a varied assortment of colors allow to further personalize the decoration.

PRODUCT FEATURES

COLOR	gold, silver, copper, neutral
COMPOSITION	resin-based binder in water emulsion
SPECIFIC WEIGHT	1.00 ± 0.10 kg/l at 20°C
VISCOSITY	6000 to 8000 cps at 25° c

Note: These properties are typical ones and are not to be considered specific. Marginal deviations of the values do not affect the efficacy or property of the product.

APPLICATION CHARACTERISTICS

TEMP. OF APPLICATION	between + 5 and + 30 °C
DRYING	dry to the touch 2/3 hours, Complete 12/24 hours,
washability of the substrate with warm water after at least 15 days.	
YIELD	70/90 ml/sqm in the gold, copper, silver version 50/70 ml/sqm in the neutral version.

The yield is to be considered as a guideline being many variables such as background, effect, etc.

DILUTION	with water max 10/15%.
EQUIPMENT	spalter-type brush for gold, silver, copper version. Spalter-type brush, sponge, rag, etc., for version Neutral.

APPLICATION SYSTEM

Careful background preparation is recommended.

Use Excalibur washable water paint for interiors by Colorificio Valdecia applied in two coats

after filling any cracks with Muraplaster Plus and applying Isolacril acrylic fixative if necessary. After at least 24 hours, when completely dry, proceed with the application of Decordecia in the chosen version.

The applicator's dexterity and customization determine the final effect.

Cleaning of tools: with tepid water.

Note: Successful application cycles are conditioned by proper preparation of the substrate. What is described in the sheet represents a minimum condition that should be supplemented to the professionalism and experience of the operator.

SAFETY REGULATIONS.

Refer to the safety data sheet for information on storage, handling and proper disposal of the product

PACKAGING

LT 2.5 - 1

WARNINGS

The product is sensitive to frost. Do not apply at temperatures below 5°C.

Shake the product thoroughly before use

All of the above technical information contained within this sheet is the result of careful laboratory tests and practical experience. They do not represent a legal warranty, expressed or implied, about the use of our product as used outside of our control. Each user should verify the effectiveness and behavior of our product with regard to its specific applications