

DESCRIPTION

Transparent siloxane protective agent. Allows water to flow along walls, preventing absorption, while maintaining equal breathability of the substrate. Ideal for concrete, brick, stoneware, tile and stone, cement or lime-based plasters. Does not alter the appearance and characteristics of the product.

PHYSICAL CHEMICAL CHARACTERISTICS

COLOR	milky white
ASPECT	liquid
COMPOSITION	binder based on siloxane polymers.
SPECIFIC WEIGHT	$1 \pm 0.05 \text{ g/cm}^3$ at 20 °C
VISCOSITY	12 ± 2 seconds cup Ford 4
DRY RESIDUE	$11 \pm 1\%$
PH	7

Note: These properties are typical ones and are not to be considered specific. Marginal deviations of the values do not affect the efficacy or property of the product.

APPLICATION CHARACTERISTICS

TEMP. OF APPLICATION	between +5 and +25 degrees °C
DRYING	3-5 hours (referred to 20°C and 65% R.H.)
YIELD	6-7 m ² /l per coat depending on substrate
DILUTION	ready to use

APPLICATION EQUIPMENT brush - roller

APPLICATION SYSTEM

SUBSTRATES: exterior and interior cement-based masonry, plaster, brickwork

SUBSTRATE PREPARATION: The substrate must be sound, dry and clean, free of salt efflorescence, and free of moisture stains and mold. Old chalking paints should be removed by pressure washing. Do not apply to fresh or particularly alkaline substrates; observe a minimum carbonation period of at least four weeks. Avoid application to fresh synthetic paints.

Note: Successful application cycles are conditioned by proper preparation of the substrate. What is described in the sheet represents a minimum condition that should be supplemented to the professionalism and experience of the operator.

APPLICATION CYCLE

NEW PLASTERS apply one or more coats until the substrate of IDROREP is rejected.

OLD PLASTERS see "PREPARATION OF THE SUBSTRATE." Proceed with the finishing as for the "NEW PLASTERS"

NOTE the product acquires all its properties after ten days approximately

SPECIFICATION ITEM

GENERAL FEATURES	transparent siloxane water repellent
DRY RESIDUE	11 ± 1%
SPECIFIC WEIGHT	1± 0.05 g/cm ³ at 20 °C

PACKAGING

PACKAGING plastic tank lt 25 - 5 - 1

GENERAL NOTES

The product is sensitive to frost. It is recommended, to store it at temperatures between +5° and +25°C. Stored in tightly closed original packaging, and not diluted with water, it has a medium storage period. Avoid application on fresh or particularly alkaline substrates, observing a minimum period of at least four weeks.

Do not apply in rain, strong wind, under direct sunlight. Protect surfaces from heavy rain for at least 48 hours after application.

All of the above technical information contained within this sheet, is the result of careful laboratory tests and practical experience. They do not represent a legal warranty, expressed or implied, about the use of our product as used outside of our control. Each user should verify the effectiveness and behavior of our product with regard to its specific applications