



MARMORINO CLASSICO

Versione 1.1.0 - 2023

DESCRIPTION

A product designed to reproduce the ancient finishes known as Marmorino. Characteristic of many buildings of historic character, MARMORINO CLASSICO once applied generates original shades and colors also enhanced by the skill of the applicator. Completely natural based on slaked lime, it prevents the formation of mold and bacteria.

PHYSICAL CHEMICAL CHARACTERISTICS

COLOR	white
ASPECT	thick paste
COMPOSITION	seasoned slaked lime and ground aggregates
SPECIFIC WEIGHT	1.45 ± 0.05 g/cm ³ at 20 °C
VISCOSITY	paste
PERMEABILITY	high
pH	about 13

Note: These properties are typical ones and are not to be considered specific. Marginal deviations of the values do not affect the efficacy or property of the product.

APPLICATION CHARACTERISTICS

TEMP. OF APPLICATION	between +5 and +25 degrees °C
DRYING	4-6 hours (referred to 20°C and 65% R.H.)
YIELD	0.5-0.8 kg/ m ² depending on substrate
DILUTION	ready to use
EQUIPMENT	steel trowel

APPLICATION SYSTEM

SUBSTRATES: lime-based plaster, lime-based bastard mortar

SUBSTRATE PREPARATION: The substrate must be sound, dry and clean, free of salt efflorescence, and free of moisture stains and mold. Old chalking paints should be removed by brushing or pressure washing. Do not apply to fresh substrates; observe a minimum carbonation period of at least four weeks. Substrates should always be moistened before applying the product.

Note: Successful application cycles are conditioned by proper preparation of the substrate. What is described in the sheet represents a minimum condition that should be supplemented to the professionalism and experience of the operator

APPLICATION CYCLE

NEW PLASTERS apply RASATURA DI BASE directly to the substrate with a steel trowel, complete with two or more coats of thin coats of MARMORINO CLASSICO

OLD PLASTERS see "PREPARATION OF THE SUBSTRATE." Proceed with the finishing as for "NEW PLASTERS."

NOTE the dry product can be treated with waxes and soaps creating greater protection and final gloss

SPECIFICATION ITEM

GENERAL FEATURES seasoned slaked lime and ground aggregates
SPECIFIC WEIGHT 1.45 ± 0.05 g/cm³ at 20 °C

PACKAGING

PACKAGING plastic buckets kg 25

GENERAL NOTES.

The product is sensitive to frost. It is recommended, to be stored at a temperature between +5° and +25°C. Stored in the original tightly closed packages, and not diluted with water, it has a medium storage period.

Product tintable with inorganic pigments in paste form. The same tint reproduced in different batches may show color variations, as well as the same batch, applied several days apart or under different environmental conditions.

Do not apply in rain, strong wind, under direct sunlight. Protect surfaces from heavy rain for at least 48 hours after application. The product is caustic, so protect glass, metal parts, stones and anything else that may come in contact with it.

Tutte le suddette informazioni tecniche contenute all'interno di questa scheda, sono il risultato d'accurate prove di laboratorio ed esperienze pratiche. Esse non rappresentano una garanzia legale, espressa o implicita, circa l'utilizzo del nostro prodotto, in quanto usato al di fuori del nostro controllo. Ciascun utilizzatore dovrà verificare l'efficacia e il comportamento del nostro prodotto per quanto attiene le sue specifiche applicazioni.