



RASATURA DI BASE

Versione 1.1.0 - 2023

DESCRIPTION

Slaked lime skim coat. Formulated to adhere to masonry and gypsum base substrates where a polished slap lime finish cycle or classic marmorino is desired. The rightly calibrated grain size turns out to be very important for the final result.

PHYSICAL CHEMICAL CHARACTERISTICS

COLOR	white
ASPECT	thick paste
COMPOSITION	seasoned slaked lime and selected aggregates
SPECIFIC WEIGHT	1.45 ± 0.05 g/cm ³ at 20 °C
VISCOSITY	paste
PERMEABILITY	high
Ph	about 13

Note: These properties are typical ones and are not to be considered specific. Marginal deviations of the values do not affect the efficacy or property of the product.

APPLICATION CHARACTERISTICS

TEMP. OF APPLICATION	between +5 and +25 degrees °C
DRYING	4-6 hours (referred to 20°C and 65% R.H.)
YIELD	0.8-1.2 kg/ m ² depending on substrate
DILUTION	ready to use
EQUIPMENT	steel trowel

APPLICATION SYSTEM

SUBSTRATES: lime-based plaster, lime-based bastard mortar

SUBSTRATE PREPARATION: The substrate must be sound, dry and clean, free of salt efflorescence, and free of moisture stains and mold. Old chalking paints should be removed by brushing or pressure washing. Do not apply to fresh substrates; observe a minimum carbonation period of at least four weeks. Substrates should always be moistened before applying the product.

Note: Successful application cycles are conditioned by proper preparation of the substrate. What is described in the sheet represents a minimum condition that should be supplemented to the professionalism and experience of the operator.

APPLICATION CYCLE

NEW PLASTERS apply RASATURA DI BASE directly to the substrate with a steel trowel

OLD PLASTERS see "PREPARATION OF THE SUBSTRATE." Proceed with the finishing as for the "NEW PLASTERS."

NOTE the skim coat, is to be considered an excellent skim coat for finishing of the GRASSELLO LUCIDO or MARMORINO CLASSICO

SPECIFICATION ITEM

GENERAL CHARACTERISTICS seasoned slaked lime and selected aggregates
SPECIFIC WEIGHT 1.45 ± 0.05 g/cm³ at 20 °C

PACKAGING

PACKAGING plastic buckets kg 25

GENERAL NOTES.

The product is sensitive to frost. It is recommended, to be stored at a temperature between +5° and +25°C. Stored in the original tightly closed packages, and not diluted with water, it has a medium storage period.

Product tintable with inorganic pigments in paste form. The same tint reproduced in different batches may show color variations, as well as the same batch, applied several days apart or under different environmental conditions.

Do not apply in rain, strong wind, under direct sunlight. Protect surfaces from heavy rain for at least 48 hours after application. The product is caustic, so protect glass, metal parts, stones and anything else that may come in contact with it.

All of the above technical information contained within this sheet, is the result of careful laboratory tests and practical experience. They do not represent a legal warranty, expressed or implied, about the use of our product as used outside of our control. Each user should verify the effectiveness and behavior of our product with regard to its specific applications.