



UNIFORMANTE

Version 1.1.0 - 2023

DESCRIPTION

Filling and uniforming primer/finish for interiors and exteriors. Its application homogenizes the absorption of substrates, facilitating subsequent coats of finish, and thanks to its high covering and masking power, it gives the treated substrate a remarkable effect of uniformity. It is suitable for homogenizing old and deteriorated surfaces or plaster and plasterboard walls where a civil plaster effect finish is required.

PHYSICAL CHEMICAL CHARACTERISTICS

COLOR	white
ASPECT	liquid
COMPOSITION	binder based on aqueous emulsions
SPECIFIC WEIGHT	1.50 ± 0.05 g/cm ³ at 20 °C
VISCOSITY	20000 ± 5000 cps R6 rpm 60

Note: These properties are typical ones and are not to be considered specific. Marginal deviations of the values do not affect the efficacy or property of the product.

APPLICATION CHARACTERISTICS

TEMP. APPLICATION.	between +5 and +25 degrees °C
DRYING	3-5 hours (reported at 20°C and 65% R.H.)
YIELD	4-6 m ² /l depending on substrate
DILUTION	5-15% with potable water depending on the substrate
EQUIPMENT	brush - roller

APPLICATION SYSTEM

SUBSTRATES: interior and exterior masonry work, drywall, skim coat, plaster.

SUBSTRATE PREPARATION: The substrate must be sound, dry, clean, free of salt efflorescence, and free of moisture stains and mold. Old chalking paints should be removed by pressure washing. Do not apply to fresh or particularly alkaline substrates; observe a minimum carbonation period of at least four weeks. Imperfections, cracks, will have to be restored using MURAPLASTER.

Note: Successful application cycles are conditioned by proper preparation of the substrate. What is described in the sheet represents a minimum condition that should be supplemented to the professionalism and experience of the operator.

APPLICATION CYCLE

NEW PLASTERS.

Apply a coat of UNIFORMANTE properly diluted with potable water, complete the cycle with the most suitable finish.

OLD PLASTERS

see "**SUPPORT PREPARATION.**" Proceed to the finish as for "**NEW PLASTERS**"

NOTE

Mix well before use.

SPECIFICATION ITEM

GENERAL CHARACTERISTICS

Uniforming filler primer/finish based on aqueous emulsions.

SPECIFIC WEIGHT

1.50 ± 0.05 g/cm³ at 20 °C

PACKAGING

PACKAGING

plastic buckets lt 14 - 5

GENERAL NOTES.

The product is sensitive to frost. It is recommended, to be stored at a temperature between +5° and +25°C. Stored in tightly closed original packaging, and undiluted with water, it has a medium storage period. Avoid application to fresh or particularly alkaline substrates, observing a minimum period of at least four weeks.

Use potable water for dilution and maintain the same proportions throughout the application.

All of the above technical information contained within this sheet is the result of careful laboratory tests and practical experience. They do not represent a legal warranty, expressed or implied, about the use of our product as used outside of our control. Each user should verify the effectiveness and behavior of our product with regard to its specific applications.