



WAXED DECIA WOOD S

Versione 1.1.0 - 2023

DESCRIPTION

Transparent waxed finish ideal for the protection of wooden artifacts both indoors and outdoors. The careful formulation makes the parts treated with WAXED DECIA WOOD S excellently protected from ultraviolet rays and atmospheric agents. WAXED DECIA WOOD S does not flake off, but it does wear off, making maintenance easier, because all that is needed is to remove surface dirt and apply one or more coats. WAXED DECIA WOOD S can be used either as a primer or as a top coat over DECIA WOOD S.

PHYSICAL-CHEMICAL CHARACTERISTICS

COLOR	colorless
FILM ASPECT	Satin-finished 50 gloss
COMPOSITION	Oleo - alkyd resin plus waxes
SPECIFIC WEIGHT	940 g/l at 20°C
VISCOSITY	Ford cup 4 45" at 20°C
FLAMING POINT	33°C
SELF-IGNITION	427° C

Note: These properties are typical ones and are not to be considered specific. Marginal deviations of the values do not affect the efficacy or property of the product.

APPLICATION CHARACTERISTICS

TEMP. OF APPLICATION	between + 5 and + 30 °C
DRYING	dry to the touch 12 hours, complete 24 hours depending on the wood and environmental conditions.
YIELD	8 - 12 sqm/l depending on the absorption of the substrate.
DILUTION	Max.10% with turpentine
APPLICATION EQUIPMENT	brush and spray

APPLICATION SYSTEM

Ideal for treating fences, wooden cottages, garden furniture and wood in general.

Make sure the substrate is sound, dry and properly sanded.

Mix the product well before use.

Apply one or more coats of WAXED DECIA WOOD S respecting the drying time.

On old wood already treated with impregnating agent, clean the surface of dust and apply one or more coats of WAXED DECIA WOOD S.

Note: Successful application cycles are conditioned by proper preparation of the substrate. What is described in the sheet represents a minimum condition that should be supplemented to the professionalism and experience of the operator.

SAFETY REGULATIONS

Refer to the safety data sheet for information on storage, handling and proper disposal of the product

PACKAGING

LT10 - 2.5 - 750 ML

WARNINGS

Store the product in a cool, dry place. Shelf life minimum 12 months in original, well-sealed packaging. Shake the product thoroughly before use

All of the above technical information contained within this sheet, is the result of careful laboratory tests and practical experience. They do not represent a legal warranty, expressed or implied, about the use of our product as used outside of our control. Each user should verify the effectiveness and behavior of our product with regard to its specific applications.