



WAXED DECIA WOOD

Versione 1.1.0 - 2023

DESCRIPTION

Water-based waxed impregnating with a satin effect, ideal for the protection of wooden items both indoors and outdoors. The careful formulation makes parts treated with waxed decia wood excellently protected from ultraviolet rays, weathering, molds and pests. Waxed Decia Wood does not flake off, but it does wear off, making maintenance easier because all that is needed is to remove surface dirt and apply a coat or coats of the product. Waxed Decia Wood can be used either as a primer or as a top coat over Decia Wood.

PHYSICAL CHEMICAL CHARACTERISTICS

COLOR	colorless
FILM APPEARANCE	Waxed, satiny, enhances wood grain
COMPOSITION	binder based on acrylic resin emulsion.
SPECIFIC WEIGHT	1.02 ± 0.03 kg/l at 20 °C
VISCOSITY	19 ± 4 cup DIN 4 at 20°C

Note: These properties are typical ones and are not to be considered specific. Marginal deviations of the values do not affect the efficacy or property of the product.

APPLICATION CHARACTERISTICS

TEMP. OF APPLICATION	between + 5 and + 30 °C
DRYING	dry to touch 1 hour, complete 12/24 hours depending on the type of Wood and environmental conditions.
YIELD	8 - 12 sqm/l depending on the absorption of the substrate.
DILUTION	ready to use
APPLICATION EQUIPMENT	brush

APPLICATION SYSTEM

Ideal for treating fences, wooden cottages, garden furniture and wood in general.

Make sure the substrate is sound, dry and properly sanded.

Mix the product well before use.

Apply one or more coats of decia wood waxed respecting the drying time.

On old wood already treated with impregnating agent, clean the surface of dust and apply one or more coats of Waxed Decia Wood.

Note: Successful application cycles are conditioned by proper preparation of the substrate. What is described in the sheet represents a minimum condition that should be supplemented to the professionalism and experience of the operator.

SAFETY REGULATIONS

Refer to the safety data sheet for information on storage, handling and proper disposal of the product

PACKAGING

LT 10 - 2.5 - 750 ML

WARNINGS

The product is sensitive to frost. Do not apply at temperatures below 5°C.
Shake the product thoroughly before use

All of the above technical information contained within this sheet, is the result of careful laboratory tests and practical experience. They do not represent a legal warranty, expressed or implied, about the use of our product as used outside of our control. Each user should verify the effectiveness and behavior of our product with regard to its specific applications.