



# DEGRADING DECIA COVER

Version 1.0.0 - 2024

## DESCRIPTION

**Degrading Decia Cover**, is a non-toxic shielding/shading product developed for the fruit and vegetable sector. Easy to prepare and apply, it allows the desired shading effect to be obtained depending on the dilution and the number of passes to be made.

No detergent is required for removal at the end of the season.

## PHYSICAL CHEMICAL CHARACTERISTICS

<b>COLOR</b>	white
<b>ASPECT</b>	matte
<b>COMPOSITION</b>	Binder based on copolymers in aqueous emulsion
<b>SPECIFIC WEIGHT</b>	1.66 ± 0.05 Kg/Lt.
<b>DRY RESIDUE</b>	65 ± 1%

Note: These properties are typical ones and are not to be considered specific. Marginal deviations of the values do not affect the efficacy or property of the product.

## APPLICATION CHARACTERISTICS

<b>TEMP. APPLICATION.</b>	between +18 and +32 degrees °C
<b>DILUTION</b>	300-500% depending on the shading to be achieved
<b>EQUIPMENT</b>	spray
<b>SUPPORTS:</b>	Plastic films of different chemical nature, glass.

**SUBSTRATE PREPARATION:** The substrate must be dry, either in the case of a new substrate or one that has been treated with previous paint.

On new substrates, it is recommended that the first coat be applied in optimal weather conditions so that there are no problems with poor adhesion to the substrate itself. However, it is always recommended to apply Decia Cover with dry weather conditions and forecasts of no high humidity or rain in the following days.

Note: Successful application cycles are conditioned by proper preparation of the substrate. What is described in the sheet represents a minimum condition that should be supplemented to the professionalism and experience of the operator.

## **APPLICATIONS**

It is recommended that the product be mixed thoroughly with the dilution water and maintain agitation during application. To achieve more shading layers, it is necessary for the layer already present to be completely dried and dry. In this way stronger shielding will be achieved. Strong dilution of the product will reduce weathering characteristics in both the first application and applications.

## **PACKAGING**

Plastic buckets Lt. 14, tanks Lt. 1000

## **GENERAL NOTES**

The product is sensitive to frost. It is recommended, to store it at temperature between +5° and +25°C. Stored in the packaging original tightly closed, and not diluted with water, has a long storage period.

All of the above technical information contained within this sheet is the result of careful laboratory tests and practical experience. They do not represent a legal warranty, expressed or implied, about the use of our product as used outside of our control. Each user should verify the effectiveness and behavior of our product with regard to its specific applications.